TABLE I. Measured isotropic elastic moduli of polycrystalline MgO, CaF<sub>2</sub>, β-ZnS, ZnSe, and CdTe.

Specimen	Density (g/cm³)	Elastic modulus <sup>a</sup>			
		Young's	Shear	Longitudinal	Method of measurements
IR-MgO	3.5819(±0.0009)	30.72(±0.12)	$12.93(\pm 0.10)$ $12.90(\pm 0.03)$	33.83(±0.03)	Resonance Pulse superposition
IR-CaF <sub>2</sub>	3.1792(±0.0008)	10.75(±0.09)	$4.07(\pm 0.07)$ $4.11(\pm 0.03)$	14.87(±0.03)	Resonance Pulse superposition
IR-ZnS	4.0791(±0.0009)	8.38(±0.09)	$3.18(\pm 0.07)$ $3.17(\pm 0.03)$	11.98(±0.03)	Resonance Pulse superposition
IR-ZnSe	$5.2664(\pm0.0009)$	7.46(±0.10)	$2.81(\pm 0.07)$ $2.89(\pm 0.03)$	9.83(±0.03)	Resonance Pulse superposition
IR-CdTe	5.8520(±0.0008)	***	$1.40(\pm 0.05) \\ 1.38(\pm 0.03)$	$6.07(\pm 0.06)$ $6.08(\pm 0.03)$	Phase comparison Pulse superposition

<sup>&</sup>lt;sup>a</sup> All values are at 298°K. All moduli are in units of 10<sup>11</sup> dyn/cm<sup>2</sup>.

IR-CaF<sub>2</sub> was 3.1792 (±0.0008) g/cm<sup>3</sup> at 298°K, and this value compares well with an x-ray density of 3.179 g/cm<sup>3</sup> at 298°K. The chemical purity of the specimen was 99.92% CaF<sub>2</sub>, and a spectrochemical analysis showed the following impurities: Sr 700, Na 50, Mg 20, Si 3, and Mn 2 ppm with trances of Al, Ba, K, and Li. The IR-CaF<sub>2</sub> was highly translucent in the visible region as in the case of IR-MgO and it had the optical properties corresponding to a single-crystal CaF<sub>2</sub>.

## C. Polycrystalline β-ZnS

The  $\beta$ -ZnS specimen used in the present program is a typical of Irtran No. 2 material. The measured density was 4.0791 ( $\pm 0.0009$ ) g/cm³ at 298°K, and this should be compared with a x-ray density of 4.088 g/cm³ at the same temperature. The specimen has been referred to as IR–ZnS in the text, and it has a chemical purity of 99.997% ZnS. Among the impurities detected were Si 1 and Pb 1 ppm with traces of Cu, Fe, and Mg. X-ray diffraction patterns indicate the IR–ZnS was composed primarily of  $\beta$ -ZnS (i.e., sphalerite).

#### D. Polycrystalline Zn Se

One specimen of polycrystalline ZnSe used in the present program is a typical Irtran No. 4 material, and this has been designated as IR–ZnSe. The IR–ZnSe had the bulk density of 5.2664 (±0.0009) g/cm³ at 298°K and this value compares well with 5.267 gm/cm³, the x-ray density at the same temperature. This specimen has a chemical purity of 99.995% ZnSe, with minor constituents including Mg 5, Cu 3, B 10, and Al 2 ppm and traces of Cr and Ni. The IR–ZnSe was translucent in the visible region and had the optical properties similar to single-crystal ZnSe.

## E. Polycrystalline CdTe

One specimen referred hereafter to as IR-CdTe is a typical of Irtran No. 6 material. The measured density was 5.8520 (±0.0008) g/cm³ at 298°K and this may be compared with 5.854 gm/cm³ calculated from the lattice constant<sup>7</sup> of 6.5815 Å at 298°K. The chemical purity of the specimen was 99.98% CdTe and the specimen contained the following impurities: B 10, Si 10, Mg 3 ppm and traces of Al, Ag, and Cu.

# 2.2. Measurements of Isotropic Elastic Moduli

The present work utilizes primarily a modified Förster-type resonance method in the kilocycle range<sup>8</sup> to determine the isotropic shear modulus and then Young's modulus of a bar-shaped polycrystalline specimen. Two ultrasonic methods<sup>9</sup> (phase-comparison and pulse-superposition techniques due to McSkimin) often used in single-crystal measurements are also used, as complementary methods, for determining the elastic parameters of polycrystalline solids under investigation. Since a detailed description on all of these methods are found in the literature, this description is not 'reproduced here.

### 3. EXPERIMENTAL RESULTS

Table I lists the measured elastic moduli for all the polycrystalline specimens considered in the present work. For a given material, two sets of isotropic elastic moduli are entered. One set is the result obtained from the resonance method in the audio-frequency range and

Mat

MgO MgO MgO MgO MgO CaF<sub>2</sub> CaF<sub>2</sub> CaF<sub>2</sub> CaF<sub>2</sub>

β-ZnS β-ZnS ZnSe ( CdTe CdTe

β-ZnS β-ZnS β-ZnS

a Values
of the origi
represent
b 36D1:
c 61S1: C
d 63C1: I

46,452 (196 65B1: I 65C1: I 28V1: V h 58S1: F

i 60H1:

the other in the damping were no ured by parison from the moduli, the sheet combine indicate determine the general transfer or the ultra the sheet of the ultra the sheet of the ultra the general transfer or the ultra the general transfer or the ultra the general transfer or the ultra transfer or transfer or the ultra transfer or the ultra transfer or the ultra transfer or the ultra transfer or transfer or the ultra transfer or transfer

4. SINC

For n than one in the li

P. W. Davis and T. S. Shilliday, Phys. Rev. 118, 1020 (1960).
 S. Spinner and W. E. Tefit, Proc. ASTM 61, 1221 (1961).
 H. J. McSkimin, Physical Acoustics W. P. Mason, Ed. (Academic Press Inc., New York, 1964), Vol. I-A, Chap. 4.