SHOCK INDUCED TRANSFORMATION IN BaF

semilattice. For further information see the following references. (1) U. Croatto and M. Bruno, Gass. Chem. Ital. 76, 246 (1946), and (2) A. S. Dworkin and M. A. Bredig, J. Physical Chem. 67, 697 (1963).

- 14. G. R. Fowles, G. E. Duvall, J. Asay, P. Bellamy, F. Feistman, D. Grady, T. Michaels and R. Mitchell, Rev. Sci. Instr. <u>41</u>, 984 (1970).
- 15. BaF₂ crystals were bought from Harshaw Chemical Co., Solon, Ohio and Optovac Inc., North Brookfield, Mass. These crystals were of optical quality and free from any visual defects. Back reflection x-ray pattern indicated that misorientation of specific specimen could be accurately represented by $\theta = \pm 0.5^{\circ}$ and $\phi = \pm 0.5^{\circ}$.
- 16. A. R. Champion, J. Appl. Phys. 42, 5546 (1971).
- W. J. Halpin and R. A. Graham, "Shock Wave Compression of Plexiglass from 3 to 20 kbars," in Fourth Symposium on Detonation, Office of Naval Research Report #ACR-126 (1965).
- W. J. Halpin, O. E. Jones and R. A. Graham, "A Submicrosecond Technique for Simultaneous Observation of Input and Propagated Impact Stresses," in Dynamic Behavior of Materials, ASTM Special Technical Publication #336 (1963).
- 19. D. B. Hayes, Ph.D. Thesis, Washington State University (1972).
- R. A. Graham, F. W. Nielson and W. B. Benedick, J. Appl. Phys. <u>36</u>, 1775 (1965).
- C. E. Wong and D. E. Schuele, J. Phys. Chem. Solids <u>29</u>, 1309 (1968).
- This conclusion is not based on the three shots reported in here alone but includes the transmitted stress profiles obtained previously in this laboratory by a graduate student in 1969-70.
- J. N. Johnson, O. E. Jones and T. E. Michaels, J. Appl. Phys. <u>41</u>, 2330 (1970).
- 24. An independent way of confirming the conclusion that the transformation in BaF_2 from fluorite to orthorhombic structure is shear induced would be to subject a small sample of either BaF_2 or preferably lead fluoride to a prolonged grinding in a mechanical mortar.

D. P. DANDEKAR AND G. E. DUVALL

- 25. J. R. Kessler (private communication) finds that β -BaF₂ is relatively easily and reasonably completely transformed to α -BaF₂ phase at 23 kbars where the pressure is applied normal to <111> direction in β -BaF₂.
- G. E. Duvall, in <u>Stress Waves in Anelastic Solids</u>, H. Kolsky and W. Prager, Eds., Springer-Verlag, Berlin (1964), pp. 20-32.

200