

Reprinted from JOURNAL OF APPLIED PHYSICS, Vol. 41, No. 13, 5309-5314, December 1970  
Copyright 1970 by the American Institute of Physics  
Printed in U. S. A.

## Shock Compression of Shoal Granite

ROBERT S. DENNEN\*

*Physics Department, University of Illinois† at Chicago Circle, Chicago, Illinois 60680*

(Received 14 November 1969; in final form 12 June 1970)

Experiments utilizing explosives with and without flyer plates have been used to determine the shock compression properties of shoal granite. High-speed framing camera records were used to determine the free surface angles which occur in wedge-cut samples upon the emergence of the resulting shock waves. The shock equations are given for the oblique geometry. Previously observed yield point data are used to obtain the Hugoniot of shoal granite in the range between 0 and 400 kbars.

### I. INTRODUCTION

A number of reports and publications have given high-pressure data for granite.<sup>1-4</sup> Attempts to plot these data on a single curve sometimes show considerable scatter.<sup>2,5</sup> Such scatter is no doubt due in part to experimental errors and sample to sample variation but may also be partially attributable to differences in the materials studied. Materials with a fairly wide variation in the proportion of mineral abundancies fall under the general classification of granite.

In this paper the results of high-pressure shock compression experiments on shoal granite are given.<sup>6</sup> The mineral content of this material was reported in a previous paper<sup>7</sup> where the results of experiments for shock pressures up to about 40 kbars were given. In the earlier work a shock tube method was used; here high explosives were used to obtain pressures up to about 400 kbars. The object of this work is to furnish

shock data for one particular type of granite throughout the complete range up to 400 kbars.

### II. EXPERIMENTAL METHOD

Two different configurations were used to generate a shock wave in a wedge-cut sample of granite. In the first, as shown schematically in Fig. 1, an explosive train consisting of a detonator, plane wave generator, and pad of high explosive were used to impact a flyer plate upon the sample. In the second, the explosive train was placed in direct contact with the sample. In both configurations, a shock wave was generated in the sample which caused free surface motion of the back face of the sample. A framing record of the slit and fiducial markings between the sample and knife edge were recorded on a Beckman Whitley model 189 framing camera. The slit area was back lighted by an argon light bomb detonated prior to the free surface motion. The

FEB 3 1971