

- Duba, A., and PIWINSKII, A. J., Geothermal exploration: an additional ambiguity in the interpretation of resistivity anomalies, Second U.N. Sym. Develop. and Use of Geothermal Resources, San Francisco, May 20-29, 1975. [UCRL-76405, Abstract]
- Duba, A., SCHOCK, R. N., and Abey, A. E., Quasi-static deformation of porous beryllium and aluminum, Lawrence Livermore Laboratory, Rept. UCRL-76587, Preprint (1975).
- Duba, A., and PIWINSKII, A. J., Electrical conductivity and dielectric properties of oil shale, Eos Trans. AGU 56, 458 (1975). [UCRL-76604, Abstract]
- Duba, A., HEARD, H. C., Schock, R. N., and Stromberg, H. D., The electrical conductivity of polycrystalline olivine and pyroxene to 5.0 GPa, Eos Trans. AGU 56, 388 (1975). [UCRL-76621, Abstract]
- Duba, A., and PIWINSKII, A. J., Feldspar electrical conductivity and the lunar interior, Proc. Sixth Lunar Sci. Conf., 2899-907 (1975). [UCRL-76755, Preprint]
- Duba, A., and PIWINSKII, A. J., The permittivity and electrical conductivity of oil shale, Int. J. Rock Mech. Min. Sci. and Geomech. Abstr. 13, 165-66 (1976). [UCRL-76789, Preprint]
- Duba, A., WEED, H. C., Piwinskii, A. J., and Santor, M. L., The electrical conductivity of sandstones, limestone and granite, Eos Trans. AGU 56, 976 (1975). [UCRL-77308, Abstract]
- Duba, A., PIWINSKII, A. J., Santor, M. L., and Weed, H., The dielectric properties of sandstones, limestone and granite, Eos Trans. AGU 56, 976 (1975). [UCRL-77314, Abstract]
- HEARD, H. C., Abey, A. E., Bonner, B. P., and Duba, A., Stress-strain behavior of polycrystalline NaCl to 3.2 GPa, Lawrence Livermore Laboratory, Rept. UCRL-51743 (1975).

The mechanical properties of dry, fine-grained salt (NaCl) containing about 1% porosity have been determined at pressures up to 3.2 GPa at 25°C. Measurements include: (1) hydrostatic pressure-volume (P-V) behavior on loading to, and unloading from, 0.8 GPa; (2) quasi-hydrostatic P-V relationship to 3.2 GPa; (3) shear strengths to strains of 0.10 at confining pressures to 0.4 GPa; (4) loading and unloading moduli determined in uniaxial stress and uniaxial strain at pressures to 0.7 GPa; and (5) ultrasonic velocities at pressures to 0.4 GPa. The hydrostatic and quasi-hydrostatic loading show slight pore crush-up beginning at 200 MPa. At the maximum pressure, $\Delta V/V_0$ of 0.11 is indicated. Unloading is identical to the loading path down to about 400 MPa; a permanent compaction of 0.007 is observed after unloading to 0.1 MPa. Although shear strengths increase slightly with strain, they are