

```

0.750 0.232 38000. 340000.
*.30 1250000.
*.04 0. 0.
-1.0123E-02 -6.2075E-02 8.0716E-02
6.2767E-02 0.0000 1.0800
-1.0747E-02 -6.9388E-02 1.1473E-01
8.5061E-02 0.0000 1.1200
-1.3557E-02 -8.8735E-02 1.4819E-01
1.0449E-01 0.0000 1.1600
-1.4745E-02 -1.0093E-01 1.7861E-01
1.2062E-01 0.0000 1.2000
-1.6893E-02 -1.1649E-01 2.0816E-01
1.3492E-01 0.0000 1.2400
-1.8855E-02 -1.3176E-01 2.3613E-01
1.4742E-01 0.0000 1.2800
-1.9038E-02 -1.4052E-01 2.6108E-01
1.5785E-01 0.0000 1.3200
-2.2936E-02 -1.6226E-01 2.8857E-01
1.6847E-01 0.0000 1.3600

-2.4522 1.0800 8.1000E-01
-1.9207E+05 0.0000 0.0000
-3.0788 1.1200 8.4000E-01
-2.5934E+05 0.0000 0.0000
-3.6944 1.1600 8.7000E-01
-3.3382E+05 0.0000 0.0000
-4.2644 1.2000 9.0000E-01
-4.1236E+05 0.0000 0.0000
-4.8138 1.2400 9.3000E-01
-4.9704E+05 0.0000 0.0000
-5.3401 1.2800 9.6000E-01
-5.8753E+05 0.0000 0.0000
-5.8294 1.3200 9.9000E-01
-6.8206E+05 0.0000 0.0000
-6.3338 1.3600 1.0200
-7.8667E+05 0.0000 0.0000
7.5000E-01 2.3200E-01 3.8000E+04 3.4000E+05
3.0000E-01 1.2500E+06
4.0000E-02 0.0000 0.0000

```

FIG. 25 SAMPLE INPUT-OUTPUT DATA
FOR APPLIED FORCE PROGRAM.
INFORMATION USED IN FIG. 6