

$$\begin{aligned}
y_i = & b + M(\lambda_i) \\
& + \sum_{\vec{h}} \alpha_{\vec{h}} \exp \left[(-4 \ln 2) (d_i - d_{\vec{h}})^2 / S_i^2 \right] \\
& + v \sum_{\vec{h}'} f_{\vec{h}'} \exp \left[(-4 \ln 2) (d_i - d_{\vec{h}'})^2 / S_i^2 \right]
\end{aligned} \tag{1}$$

where b is the time independent background, λ_i is the neutron wavelength scattered into channel i , $M(\lambda_i) = \beta d_i^{-\gamma} e^{-\delta/\lambda_i^2}$ is a Maxwellian intensity function with three variable parameters β , γ , δ used to fit the time-dependent background, d_i is the wavelength scattered into channel i divided by the factor $2 \sin \theta$ where 2θ is the scattering angle (30 or 60 deg), and S_i is the instrumental linewidth at half peak height for each channel. The symbols \vec{h} and \vec{h}' stand for the Miller indices (hkl) for the KCN peaks and for the Al_2O_3 peaks respectively which might be present in the pattern. The calculated plane spacings for KCN and Al_2O_3 , $d_{\vec{h}}$ and $d_{\vec{h}'}$, respectively, are determined from the lattice parameters which are the only adjustable parameters which affect the peak positions. $\alpha_{\vec{h}}$ and $f_{\vec{h}'}$ are the peak amplitudes of the KCN peaks and the Al_2O_3 peaks respectively, and v is an overall intensity factor for Al_2O_3 . The KCN peak amplitudes $\alpha_{\vec{h}}$ are treated as variable parameters while the relative amplitudes $f_{\vec{h}'}$ for Al_2O_3 are held fixed at values determined from a pure Al_2O_3 diffraction pattern. Pb peaks, if present, are treated in the same manner as Al_2O_3 peaks. This allows an accurate subtraction of Al_2O_3 and Pb peaks from the pattern which in all cases were very small at the 60° scattering angle. In some regions of the diffraction pattern the intensities obtained from