sion (held constant for the rce. The results of five res are shown in Figure 2. apparent relaxation moduous results from Figure 1, trends in the creep and reessure does increase the genit be hypothesized that part method of loading. In the applied while in relaxation iple. This later displacend and, consequently, at a "glass." If this were the resulted and as a consechanges could have ocre the stress had a response le of monitoring such re-

fect the rheology of the study goes, pressure does use as a high-pressure seal. of unsupported and g at low pressures proved pressures to 10 kbar.

Foundation

ented at the Winter

nted at the Winter

re-1969," P. L. Pratt,

of polyethylene at High

e change before yielding ner. Phys. Soc., <u>16</u>, 429

v and Fracture," McGraw-

ions," Macmillan, New

POLYMER LETTERS

- (8) P. M. Naghdi, F. Essenberg, and W. Kolff, J. Appl. Mechanics. <u>25</u>, 201 (1958).
- (9) J. D. Ferry, "Viscoelastic Properties of Polymers," Wiley, New York, 1970.
- (10) K. L. DeVries, G. S. Baker, and Gibbs P., J. Appl. Phy., <u>34</u>, 2254 (1963).
- (11) K. L. DeVries, G. S. Baker, and P. Gibbs, J. Appl. Phys., <u>34</u>, 3119 (1963).
- (12) D. K. Backman, Master's Thesis, University of Utah, Salt Lake City, 1965.

K. L. DeVries D. K. Backman

Dept. of Mechanical Engineering College of Engineering University of Utah Salt Lake City, Utah 84112

Received April 19, 1971 Revised August 24, 1971