

$$\left(\frac{\partial P}{\partial V}\right)_S = \frac{dP_S}{dV}, \quad \left(\frac{\partial P}{\partial V}\right)_H = \frac{dP_H}{dV}$$

$$\left(\frac{\partial E}{\partial V}\right)_H = \frac{dE_H}{dV}, \quad \left(\frac{\partial E}{\partial V}\right)_S = \frac{dE_S}{dV} = -P_S.$$
(36)

Equation (35) then simplifies to

$$\frac{dP_S}{dV} + kP_S = \frac{d}{dV}(P_H - kE_H).$$
(37)

The pressure and energy on the Hugoniot are expressed as

$$P_H = \frac{C^2 a}{(V_0 - Ma)^2}$$

$$E_H = P_H a/2$$

when  $a = V_0 - V$  is substituted into Eqs. (6) and (32). Substitution of derivatives of  $P_H$  and  $E_H$  with respect to  $a$  into Eq. (37) yields

$$\frac{dP_S}{da} - kP_S = \frac{C^2}{(V_0 - Ma)^3} [V_0 + a(M - kV_0)].$$
(38)

This first order differential equation can be solved using the integrating factor  $\exp(\int k da)$ . Hence,

$$P_S = Ae^{ka} + e^{ka} \int e^{-ka} C^2 \left[ \frac{V_0 + a(M - kV_0)}{(V_0 - Ma)^3} \right] da$$
(39)

where  $A$  is a constant of integration. The integral term can be performed in a never ending series of integrations by parts, but an easier method using information gained from integrating by parts is to assume a series solution of the form

$$P_S = Ae^{ka} + \frac{C^2}{(V_0 - Ma)^2} \sum_{i=0}^{\infty} A_i a^i.$$
(40)

The  $A_i$ 's must be chosen such that Eq. (38) is satisfied for all powers of  $a$ . The recursion relation for the  $A_i$ 's which satisfies this requirement is