

Table II. Shot data for liquid nitrogen.

Shot No.	Explosive ^a and thickness (cm)	Driver system ^b and thickness (cm)	Dural target thickness (cm)	Dural shock vel. (km/sec)
1 ^c	10.16 Bar	2.54 Ur	1.14	6.07 ± 0.07
2	5.08 Bar	2.54 Br	1.06	6.24 ± 0.04
3 ^c	10.16 Bar	Target plate only	1.14	6.58 ± 0.03
4 ^c	10.16 TNT	Target plate only	1.14	6.97 ± 0.03
5 ^c	10.16 CB	Target plate only	1.14	7.48 ± 0.02
6 ^c	10.16 9404	Target plate only	1.14	7.71 ± 0.02
7	10.16 CB	0.16 AG, 0.033 Poly, 0.66 FP, 2.54 AG	0.32	7.91 ± 0.01
8	5.08 9404	0.033 Poly, 0.32 Du FP, 1.59 AG	0.32	8.48 ± 0.05
9 ^c	15.24 9404	0.013 Poly, 0.64 Du FP, 3.18 AG, 0.64 Du	1.14	8.58 ± 0.07
10	15.24 CB	0.013 Poly, 0.32 SS FP, 2.54 AG, 0.32 Du	0.64	8.89 ± 0.06
11	15.24 CB	0.013 Poly, 0.32 SS FP, 2.54 AG, 0.32 Du	0.32	9.13 ± 0.06
12	10.16 CB	0.16 AG, 0.033 Poly, 0.24 SS FP, 2.54 AG	0.32	9.19 ± 0.10
13	15.24 CB	0.16 AG, 0.033 Poly, 0.32 SS FP, 2.54 AG	0.32	9.22 ± 0.06
14	10.16 CB	0.16 AG, 0.033 Poly, 0.20 SS FP, 2.54 AG	0.32	9.35 ± 0.08
15	10.16 CB	0.013 Poly, 0.16 SS FP, 2.54 AG	0.32	9.43 ± 0.07