

to achieve velocities much higher than about 6000 meters/second by direct explosive acceleration is quite impractical.

One anticipates that the rapid acceleration may subject the projectile to stresses which cause it to fracture or deform. These may be estimated by equating the stagnation pressure on the projectile to the maximum stress of deformation,  $\sigma_0$ . This yields

$$\sigma_0 = 2\rho_0 D^2 y'' / 9Q \quad (12)$$

In the process of numerical integration,  $y''$  was sometimes tabulated. The largest values of  $y''/Q$  recorded were  $\sim .5$ . Putting this into Eq. (12) with  $\rho_0 = 1.7$  g/cc and  $D = 8.8 \times 10^5$  cm/sec yields  $\sigma_0 \sim 150$  kilobars. It is not surprising, then, that explosive-accelerated projectiles shatter. The remarkable thing is that sometimes they don't.

## REFERENCES

- AZIZ, A. K., H. HURWITZ AND H. M. STERNBERG, 1961. Energy transfer to a rigid piston under detonation loading, *Phys. Fluids*, **4**, 380-384.
- DEAL, W. E., 1957. Measurement of Chapman-Jouguet pressures of explosives, *J. Chem. Phys.*, **27**, 796.
- JOHNSON, E. G., 1969. AIAA Hypervelocity Impact Conference, April 30-May 2, Cincinnati, Ohio. General Chairman, Elmer G. Johnson, Aerospace Research Laboratories, Wright Patterson AFB, Ohio. For information write to Meetings Dept., AIAA, 1290 Sixth Ave., New York, N.Y., 10019.
- LUKASIEWICZ, J., 1965. Proc. of Fourth Hypervelocity Techniques Symposium, Arnold Engineering Development Center, Tullahoma, Tenn.
- RINEHART, J. S. AND W. C. WHITE, 1952. Shapes of craters formed in plaster of Paris by ultraspeed pellets, *Am. J. Phys.*, **20**, 14.
- SEIGEL, A. E., 1965. The theory of high speed guns, *AGARDograph* 91, North Atlantic Treaty Organization, Advisory Group for Aerospace Research and Development.