

the apparent lack of correlation between axial stress-strain behaviour and nature of deformation pointed to by GRIGGS and HANDIN [23].

It is not clear why, as observed above, barrelling appears more pronounced when the specimen dilates during deformation than when it compacts and further observations are needed to test whether this correlation is a general effect. Dilation contributes an additional lateral expansion which will tend to exaggerate the barrelling due to end-constraint but this is a minor effect. Otherwise, the explanation may involve a more far-reaching influence of the end-constraints in a dilating specimen.

Application

The main aim of this study has been the better understanding of fundamental mechanisms of rock deformation rather than immediate practical application and only some suggestions regarding applications can be made here. Points of relevance to solid-medium high-pressure apparatus have been discussed elsewhere [14]. Applications in engineering rock mechanics are likely to arise especially when pore fluids are present since dilatancy or compaction will lead to decrease or increase, respectively, in the pore pressure if the rates of strain relative to the permeability of the rock are such that a condition of 'incomplete draining' exists and this will influence any phenomena dependent on pore pressure. Also, roles of dilatancy in metamorphism, the generation of magma and the occurrence of earthquakes have been proposed by earlier writers [18, 38].

Application to geology is made difficult by lack of knowledge of the influence of higher temperature or slower strain rate, either of which will tend to reduce the role of cataclastic flow and dilatancy under geological conditions. However, they may still be present under low-grade conditions where the available crystallographic glide systems are inadequate for full intracrystalline plasticity and diffusion-dependent alternative processes are still relatively slow, or even under higher-grade conditions when the pore pressure is high. In such cases, inelastic volume changes of either sign may have important consequences. Dilatancy may facilitate movement of fluid phases in a rock of initially low permeability, thereby accelerating metasomatic or other metamorphic processes; this could be one of the most important ways in which mineralogical reactions are accelerated in deforming regions. The alternative effect of deformation in accelerating compaction in porous rock may be relevant in the compaction of sedimentary rocks.

It is possible that a dilatancy associated with deformation under upper crustal conditions occurs in the vicinity of active faults, for example, near the San Andreas Fault [39]. Such an association would imply that the straining in the vicinity of the fault is not a steady state process; it may be an aspect of episodic behaviour at the fault. A possible consequence, if the ratio of strain rate to permeability is appropriate, is a decrease in pore pressure at the fault, thereby inhibiting slippage on the fault itself and allowing a general build-up in stress levels.

Acknowledgement—WAYNE C. BURNHAM gave us the idea of using an unpotted LVDT inside the pressure vessel.

REFERENCES

1. BRIDGMAN P. W. Volume changes in the plastic stages of simple compression. *J. appl. Phys.* **20**, 1241–1251 (1949).
2. BRACE W. F., PAULDING B. W. JR. and SCHOLZ C. Dilatancy in the fracture of crystalline rocks. *J. geophys. Res.* **71**, 3939–3953 (1966).
3. SCHOLZ C. H. Microfracturing and the inelastic deformation of rock in compression. *J. geophys. Res.* **73**, 1417–1432 (1968).

4. BORG I., FRIEDMAN M., HANDIN J. and HIGGS D. V. Experimental deformation of St. Peter sand: a study of cataclastic flow. *Mem. geol. Soc. Am.* **79**, 133-191 (1960).
5. HANDIN J., HAGER R. V. JR, FRIEDMAN M. and FEATHER J. N. Experimental deformation of sedimentary rocks under confining pressure: pore pressure tests. *Bull. Am. Ass. Petrol. Geol.* **47**, 717-755 (1963).
6. BRACE W. F. and ORANGE A. S. Electrical resistivity changes in saturated rocks during fracture and frictional sliding. *J. geophys. Res.* **73**, 1433-1445 (1968).
7. MISES R. von Mechanik der plastischen Formänderung von Kristallen. *Z. angew. Math. Mech.* **8**, 161-185 (1928).
8. TAYLOR G. I. Plastic strain in metals. *J. Inst. Metals* **62**, 307-324 (1938).
9. GROVES G. W. and KELLY A. Independent slip systems in crystals. *Phil. Mag.* **8**, 877-887 (1963).
10. PATERSON M. S. The Ductility of Rocks, in *Physics of Strength and Plasticity* (Ali S. Argon, Ed.) pp. 377-392, M.I.T. Press, Cambridge (1969).
11. PATERSON M. S. Triaxial testing of materials up to 10,000 kg/sq.cm. *J. Instn Engrs Aust.* **36**, 23-29 (1964).
12. VESIC A. S. and CLOUGH G. W. Behaviour of granular materials under high stresses. *J. Soil Mech. Fdns Div. Am. Soc. civ. Engrs* **94**, (SM3) 661-688 (1968).
13. BISHOP A. W. The strength of soils as engineering materials. *Géotechnique* **16**, 91-128 (1966).
14. EDMOND J. M. and PATERSON M. S. Strength of solid pressure media and implications for high pressure apparatus. *Contr. Mineral. Petrol.* **30**, 141-160 (1971).
15. EDMOND J. M. and PATERSON M. S. Effects of pressure on the deformation of graphite. *Carbon*. In press.
16. PATERSON M. S. Secondary changes of length with pressure in experimentally deformed rocks. *Proc. R. Soc. A* **271**, 57-87 (1963).
17. BISHOP A. W. Discussion. *Géotechnique* **4**, 43-45 (1954).
18. FRANK F. C. On dilatancy in relation to seismic sources. *Rev. Geophys.* **3**, 485-503 (1965).
19. PATERSON M. S. Effect of pressure on stress-strain properties of materials. *Geophys. J.R. astr. Soc.* **14**, 13-17 (1967).
20. GRIGGS D. and HANDIN J. (Ed.) Rock Deformation (A Symposium). *Mem. geol. Soc. Am.* **79** (1960).
21. CARTER N. L., CHRISTIE J. M. and GRIGGS D. T. Experimental deformation and recrystallization of quartz. *J. Geol.* **72**, 687-733 (1964).
22. RALEIGH C. B. Glide mechanisms in experimentally deformed minerals. *Science* **150**, 739-741 (1965).
23. GRIGGS D. and HANDIN J. Observations on fracture and a hypothesis of earthquakes. *Mem. geol. Soc. Am.* **79**, 347-364 (1960).
24. DAVIS L. A. and GORDON R. B. Pressure dependence of plastic flow stress of alkali halide single crystals. *J. appl. Phys.* **39**, 3885-3897 (1968).
25. PATERSON M. S. and WEAVER C. W. Deformation of polycrystalline MgO under pressure. *J. Am. ceram. Soc.* **53**, 463-471 (1970).
26. TURNER F. J., GRIGGS D. T. and HEARD H. Experimental deformation of calcite crystals. *Bull. geol. Soc. Am.* **65**, 883-934 (1954).
27. TAYLOR D. W. *Fundamentals of Soil Mechanics*, Wiley, New York (1948).
28. SCHOFIELD A. and WROTH P. *Critical State Soil Mechanics*, McGraw-Hill, London (1968).
29. MOGI K. Study of elastic shocks caused by the fracture of heterogeneous materials and its relations to earthquake phenomena. *Bull. Earthq. Res. Inst. Tokyo Univ.* **40**, 125-173 (1962).
30. DOWER R. J. On the brittle-ductile transition pressure. *Acta Met.* **15**, 497-500 (1967).
31. FRANÇOIS D. and WILSHAW T. R. The effect of hydrostatic pressure on the cleavage fracture of polycrystalline materials. *J. appl. Phys.* **39**, 4170-4177 (1968).
32. BYERLEE J. D. Brittle-ductile transition in rocks. *J. geophys. Res.* **73**, 4741-4750 (1968).
33. IRWIN G. R. and KIES J. A. Fracturing and fracture dynamics. *Weld. J. Res. Suppl.* **31**, 95S-100S (1952).
34. GURNEY C. and HUNT J. Quasi-static crack propagation. *Proc. R. Soc. A* **299**, 508-524 (1967).
35. BIENIAWSKI Z. T. Stability concept of brittle fracture propagation in rocks. *Engng Geol.* **2**, 149-162 (1967).
36. DRUCKER D. C. Plasticity, in *Proceedings of the First Symposium on Naval Structural Mechanics* (J. N. Goodier and N. J. Hoff, Eds) pp. 407-451, Pergamon Press (1960).
37. BYERLEE J. D. and BRACE W. F. High-pressure mechanical instability in rocks. *Science* **164**, 713-715 (1969).
38. MEAD W. J. The geologic role of dilatancy. *J. Geol.* **33**, 685-698 (1925).
39. RALEIGH C. B. and BURFORD R. O. Tectonics of the San Andreas fault system. Strain studies. *EOS Trans. Am. geophys. Un.* **50**, 380-381 (1969).