

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
EQUIPMENT AND EXPERIMENTAL PROCEDURE	2
Extrusion Tooling	2
Materials	3
Lubricants, Coatings, and Fluids	4
CHARACTERISTICS OF PRESSURE-DISPLACEMENT CURVES	4
COLD HYDROSTATIC EXTRUSION OF 7075-0 ALUMINUM ALLOY ROUNDS AND T-SECTIONS	6
Lubricants and Fluids	6
Billet Nose Design	9
Tandem Extrusion	12
Other Trials	13
COLD HYDROSTATIC EXTRUSION OF AISI 4340 STEEL ROUNDS	14
COLD HYDROSTATIC EXTRUSION OF Ti-6Al-4V TITANIUM ALLOY ROUNDS AND TUBING	14
COLD HYDROSTATIC EXTRUSION OF WROUGHT TZM MOLYBDENUM ALLOY AND BERYLLIUM ROUNDS	16
Die Design	16
Effect of Die Design, Extrusion Ratio and Lubricants on Stress-Relieved TZM	19
Extrusion of Recrystallized TZM and Beryllium	21
HYDROSTATIC EXTRUSION AND DRAWING OF BERYLLIUM WIRE	22
REFERENCES	24

LIST OF TABLES

	<u>Page</u>
Table 1. Billet Lubricants Used for Hydrostatic Extrusion During This Interim Report Period.	4
Table 2. Experimental Data for the Cold Hydrostatic Extrusion of 7075-0 Aluminum Alloy Rounds	7
Table 3. Experimental Data for the Cold Hydrostatic Extrusion of Ti-6Al-4V Titanium Alloy Rounds and Tubing	15
Table 4. Experimental Data for the Cold Hydrostatic Extrusion of AISI 4340 Steel	15
Table 5. Experimental Data for the Cold Hydrostatic Extrusion of Wrought TZM Molybdenum Alloy and Beryllium Rounds.	17

LIST OF FIGURES

Figure 1. Die Seal Arrangements Evaluated in Hydrostatic Extrusion	3
Figure 2. Classification of Pressure Versus Displacement Curves in Hydrostatic Extrusion	25
Figure 3. Effect of Fluid and Billet Lubricant on Pressure-Displacement Curves Obtained in the Hydrostatic Extrusion of 7075-0 Aluminum at a Ratio of 20:1	8
Figure 4. Effect of Billet Nose Shape and Fluid on Pressure-Displacement Curves Obtained in the Hydrostatic Extrusion of 7075-0 Aluminum at a Ratio of 40:1	10
Figure 5. Billet Nose Designs Evaluated in Hydrostatic Extrusion	11
Figure 6. Tandem Billet Joint Designs Evaluated in Hydrostatic Extrusion	12
Figure 7. Standard Die Profile and Two Dies Designed to Eliminate Cracking of Hydrostatic Extrusions	18
Figure 8. Influence of Die Design and Extrusion Ratio on Cracking of Hydrostatic Extrusions of Wrought TZM Molybdenum Alloy	20
Figure 9. Influence of Extrusion Ratio on the Extrusion Fluid-Runout Pressure for Wrought TZM Molybdenum Alloy	21