

TABLE OF CONTENTS

	<u>Page</u>
I. INTRODUCTION . . . . .	1
II. SUMMARY VOLUME I . . . . .	3
III. EQUIPMENT AND PROCEDURE . . . . .	8
Extrusion Tooling . . . . .	8
The Hydrostatic Extrusion Operational Sequence . . . . .	8
Pressure Control and Measurement . . . . .	11
High-Pressure Strain-Gage Transducer . . . . .	11
Sealing Arrangements . . . . .	15
Room Temperature . . . . .	15
Temperature Range of 400-500 F . . . . .	16
Die Design . . . . .	17
Billet Materials . . . . .	19
Lubrication . . . . .	19
Hydrostatic Fluids . . . . .	22
Billet Lubricants . . . . .	22
Billet Conversion Coatings . . . . .	24
IV. CHARACTERISTICS OF PRESSURE-DISPLACEMENT CURVES . . . . .	26
V. ASSESSMENT OF FLUID HEATING EFFECTS DURING COMPRESSION . . . . .	28
SECTION I	
VI. SUMMARY SECTION I . . . . .	31
VII. COLD HYDROSTATIC EXTRUSION OF 7075-0 ALUMINUM ROUNDS . . . . .	36
Extrusion Ratio . . . . .	36
Reliability of Data . . . . .	38
Billet Finish . . . . .	38
Lubrication Systems . . . . .	38
Billet Nose Design . . . . .	41
Stem Speed . . . . .	43
Tensile Properties of 7075-0 Aluminum Hydrostatic Extrusions . . . . .	46
VIII. HYDROSTATIC EXTRUSION OF AISI 4340 STEEL ROUNDS . . . . .	47
Extrusion Ratio . . . . .	47
Fluids and Billet Lubrication at 80 F . . . . .	53
Billet Lubricants and Coatings . . . . .	54
Hydrostatic Fluids . . . . .	57
Billet Surface Finish . . . . .	58

TABLE OF CONTENTS  
(Continued)

	<u>Page</u>
Stem Speed . . . . .	58
Hydrostatic Extrusion of AISI 4340 Steel at	
Elevated Temperatures . . . . .	60
Extrusion at 140 F . . . . .	60
Extrusion at 400 and 500 F . . . . .	61
Tensile Properties of AISI 4340 Steel Hydrostatic Extrusions . . . . .	63
 IX. HYDROSTATIC EXTRUSION OF Ti-6Al-4V TITANIUM	
ALLOY ROUNDS . . . . .	65
Extrusion Ratio . . . . .	65
Lubrication at 80 F . . . . .	65
Evaluation of Billet Lubricants Without Billet Coatings . . . . .	65
Evaluation of Billet Lubricants and Billet Coatings . . . . .	70
Fluids at Room and Elevated Temperatures . . . . .	72
Billet Lubricants at 400 and 500 F . . . . .	72
Effect of Temperature . . . . .	73
Mechanical Properties of Ti-6Al-4V Titanium Alloy Rounds	
Produced by Cold Hydrostatic Extrusion . . . . .	73
 X. HYDROSTATIC COMPACTION AND HYDROSTATIC EXTRUSION OF	
POWDER COMPACTS OF Ti-6Al-4V ALLOY POWDER . . . . .	74
Hydrostatic Compaction of Ti-6Al-4V Titanium Alloy Powder . . . . .	74
Hydrostatic Extrusion of Powder Compacts of Ti-6Al-4V	
Alloy Powder . . . . .	75
 XI. HYDROSTATIC EXTRUSION OF SUPERALLOYS ALLOY 718 AND A286 . . . . .	76
Tensile Properties of Hydrostatic Extrusions of Alloy 718 and	
A-286 Superalloys . . . . .	76
 XII. COLD HYDROSTATIC EXTRUSION OF DISPERSION-HARDENED	
SINTERED ALUMINUM . . . . .	78
 XIII. HYDROSTATIC EXTRUSION OF BRITTLE MATERIALS . . . . .	80
Extrusion Ratio . . . . .	80
Die Designs . . . . .	84
Effect of Die Design, Extrusion Ratio, and Temperature	
on TZM . . . . .	86
Evaluation of Die Designs at an Extrusion Ratio of 2.5:1 . . . . .	86
Controlled-Relief Die - Extrusion Ratio 3.3:1 . . . . .	86
Standard Die - Extrusion Ratio 5:1 . . . . .	86
Double-Reduction Die - Extrusion Ratio 4:1 . . . . .	88
Effect of Die Design, Extrusion Ratio, and Temperature	
on Beryllium . . . . .	89