

TABLE OF CONTENTS

	<u>Page</u>
I. INTRODUCTION	1
II. SUMMARY VOLUME I	3
III. EQUIPMENT AND PROCEDURE	8
Extrusion Tooling	8
The Hydrostatic Extrusion Operational Sequence	8
Pressure Control and Measurement	11
High-Pressure Strain-Gage Transducer	11
Sealing Arrangements	15
Room Temperature	15
Temperature Range of 400-500 F	16
Die Design	17
Billet Materials	19
Lubrication	19
Hydrostatic Fluids	22
Billet Lubricants	22
Billet Conversion Coatings	24
IV. CHARACTERISTICS OF PRESSURE-DISPLACEMENT CURVES	26
V. ASSESSMENT OF FLUID HEATING EFFECTS DURING COMPRESSION	28
SECTION I	
VI. SUMMARY SECTION I	31
VII. COLD HYDROSTATIC EXTRUSION OF 7075-0 ALUMINUM ROUNDS	36
Extrusion Ratio	36
Reliability of Data	38
Billet Finish	38
Lubrication Systems	38
Billet Nose Design	41
Stem Speed	43
Tensile Properties of 7075-0 Aluminum Hydrostatic Extrusions	46
VIII. HYDROSTATIC EXTRUSION OF AISI 4340 STEEL ROUNDS	47
Extrusion Ratio	47
Fluids and Billet Lubrication at 80 F	53
Billet Lubricants and Coatings	54
Hydrostatic Fluids	57
Billet Surface Finish	58

TABLE OF CONTENTS
(Continued)

	<u>Page</u>
Stem Speed	58
Hydrostatic Extrusion of AISI 4340 Steel at	
Elevated Temperatures	60
Extrusion at 140 F	60
Extrusion at 400 and 500 F	61
Tensile Properties of AISI 4340 Steel Hydrostatic Extrusions	63
 IX. HYDROSTATIC EXTRUSION OF Ti-6Al-4V TITANIUM	
ALLOY ROUNDS	65
Extrusion Ratio	65
Lubrication at 80 F	65
Evaluation of Billet Lubricants Without Billet Coatings	65
Evaluation of Billet Lubricants and Billet Coatings	70
Fluids at Room and Elevated Temperatures	72
Billet Lubricants at 400 and 500 F	72
Effect of Temperature	73
Mechanical Properties of Ti-6Al-4V Titanium Alloy Rounds	
Produced by Cold Hydrostatic Extrusion	73
 X. HYDROSTATIC COMPACTION AND HYDROSTATIC EXTRUSION OF	
POWDER COMPACTS OF Ti-6Al-4V ALLOY POWDER	74
Hydrostatic Compaction of Ti-6Al-4V Titanium Alloy Powder	74
Hydrostatic Extrusion of Powder Compacts of Ti-6Al-4V	
Alloy Powder	75
 XI. HYDROSTATIC EXTRUSION OF SUPERALLOYS ALLOY 718 AND A286	76
Tensile Properties of Hydrostatic Extrusions of Alloy 718 and	
A-286 Superalloys	76
 XII. COLD HYDROSTATIC EXTRUSION OF DISPERSION-HARDENED	
SINTERED ALUMINUM	78
 XIII. HYDROSTATIC EXTRUSION OF BRITTLE MATERIALS	80
Extrusion Ratio	80
Die Designs	84
Effect of Die Design, Extrusion Ratio, and Temperature	
on TZM	86
Evaluation of Die Designs at an Extrusion Ratio of 2.5:1	86
Controlled-Relief Die - Extrusion Ratio 3.3:1	86
Standard Die - Extrusion Ratio 5:1	86
Double-Reduction Die - Extrusion Ratio 4:1	88
Effect of Die Design, Extrusion Ratio, and Temperature	
on Beryllium	89