

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1.	Hydrostatic Extrusions of Aluminum Alloys	5
2.	Hydrostatic Extrusions of High Strength and Brittle Materials	5
3.	Hydrostatically Extruded Tubing From Three Alloys	7
4.	Hydrostatic-Extrusion Tooling Installed in 700-Ton Vertical Hydraulic Press at Battelle	9
5.	Assembly Drawing of Tooling for Hydrostatic Extrusion	10
6.	Details of Hydrostatic Extrusion Process Showing the Stem and Die Seal Methods, and Partially Extruded Billet	12
7.	Temperature Resistivity Curve for Manganin Wire	13
8.	High-Pressure Transducer Developed at Battelle for Measuring High Fluid Pressures at Room and Elevated Temperatures	14
9.	Die Seal Arrangements Evaluated in Hydrostatic Extrusion	16
10.	Stem-Seal Arrangement Used for Warm Hydrostatic Extrusion	17
11.	Die Design With Helical Groove in Conical-Entry Surface	18
12.	Relationship Between Extrusion Pressure, Extrusion Ratio, and Billet Hardness	34
13.	Effect of Extrusion Ratio on Fluid Runout Pressures in the Hydrostatic Extrusion of 7075-O Aluminum Rounds	37
14.	Effect of Fluid and Billet Lubricant on Pressure-Displacement Curves Obtained in the Hydrostatic Extrusion of 7075-O Aluminum at a Ratio of 20:1	42
15.	Two Billet Nose Designs Evaluated in Hydrostatic Extrusion	44
16.	Effect of Billet Nose Shape on Pressure-Displacement Curves Obtained in the Hydrostatic Extrusion of 7075-O Aluminum at a Ratio of 40:1	45
17.	Effect of Extrusion Ratio on Pressures Required for Hydrostatic Extrusion of AISI 4340 Steel	52
18.	Effect of Stem Speed on Fluid Pressures for Cold Hydrostatic Extrusion of AISI 4340 at an Extrusion Ratio of 5:1	59
19.	Effect of Extrusion Ratio on Runout-Fluid Pressures for Ti-6Al-4V Rounds	69

LIST OF ILLUSTRATIONS
(Continued)

<u>Figure</u>		<u>Page</u>
20.	Comparison of Surface Finishes on Cold Hydrostatic Extrusions of Ti-6Al-4V Made at a Ratio of 3.33:1	71
21.	Influence of Extrusion Ratio on Pressures for Beryllium and Wrought TZM	83
22.	Standard Die Profile and Two Dies Designed to Eliminate Cracking in Brittle Materials	85
23.	Influence of Double-Reduction Die on Cracking of Hydrostatic Extrusions of Wrought TZM Molybdenum Alloy	87
24.	Influence of Die Design on Cracking in Hydrostatic Extrusions of Beryllium	90
25.	Photomicrographs of Beryllium Cold Hydrostatically Extruded at a Ratio of 4:1 Through Battelle's Double-Reduction Die	92
26.	Classification of Pressure-Displacement Curves Obtained in Hydrostatic Extrusion	95
27.	Floating Mandrel Arrangement for Hydrostatic Extrusion of Tubing	99
28.	Effect of Extrusion Ratio on Pressure for Cold Hydrostatic Extrusion of 7075-O Aluminum Tubing and Rounds	103
29.	Effect of Extrusion Ratio on Pressure for Cold Hydrostatic Extrusion of AISI 4340 Tubing and Rounds	105
30.	Effect of Extrusion Ratio on Pressure for Cold Hydrostatic Extrusion of Ti-6Al-4V Tubing and Rounds	108
31.	Two Die Designs Used in the Hydrostatic Extrusion of T-Sections From Round Billets	111
32.	Die Insert and Orifice Dimensions for a Re-Entrant Channel Section	112
33.	Die Design for Hydrostatic Extrusion of T-Section Billets	112
34.	T-Sections Produced by HYDRAW and Re-Extrusion	119
35.	Tooling Set-Up for HYDRAW of Wire	121
36.	Two Methods of Unreeling Wire From Within a Small-Bore Container	123
37.	Counterbored Tandem Billet Joint Design Evaluated in Hydrostatic Extrusion	134
38.	Tapered Tandem Billet Joint Design Evaluated in Hydrostatic Extrusion	134