

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
39.	Schematic of High-Pressure-Container Design Concepts Analyzed in the Present Study . . . . .	157
40.	Ring-Fluid-Ring Container for High Pressure . . . . .	158
41.	Notations Used for Analysis of Container-Design Concepts . . . . .	160
42.	Fatigue Diagram for $10^4$ - $10^5$ Cycles Life for High-Strength Steels at Temperatures of 75 F to 1000 F . . . . .	165
43.	Maximum Pressure-to-Strength Ratio, $p/2S$ , in Multiring Container Designed on Basis of Static Shear Strength . . . . .	177
44.	Maximum Pressure-to-Strength Ratio, $p/\sigma$ , in Multiring Container Designed on Basis of Fatigue Shear Strength . . . . .	177
45.	Maximum Pressure-to-Strength Ratio, $p/\sigma_1$ , in Multiring Container With High-Strength Liner Based on the Fatigue Tensile Strength of Liner . . . . .	179
46.	Limit to Maximum Pressure-to-Strength Ratio, $p/\sigma$ , in Multiring Container With High-Strength Liner Based on Shear Fatigue Strength of the Outer Rings . . . . .	179
47.	Influence of Number of Rings on Maximum Pressure-to-Strength Ratio, $p/\sigma$ , in Multiring Container With High-Strength Liner . . . . .	180
48.	Influence of Liner Size on Maximum Pressure-to-Strength Ratio, $p/\sigma$ , in Multiring Container With High-Strength Liner . . . . .	180
49.	Comparison of Multiring Container With Ring-Segment Container for Various $k_1$ . . . . .	185
50.	Comparison of Multiring Container With Ring-Segment Container for Various Segment Wall Ratios . . . . .	185
51.	Effect of Elastic Modulus of Segments on Pressure-to-Strength Ratio, $p/\sigma_1$ , for the Ring-Segment Container . . . . .	186
52.	Effect of Liner Size on Pressure-to-Strength Ratio, $p/\sigma$ , for Ring-Segment Container . . . . .	186
53.	Effect of Segment Size on the Pressure-to-Strength Ratio, $p/\sigma_1$ , for the Ring-Fluid-Segment Container . . . . .	188
54.	Effect of Segment Size on the Pressure-to-Strength Ratio, $p/\sigma_3$ , for the Ring-Fluid-Segment Container . . . . .	188

LIST OF ILLUSTRATIONS  
(Continued)

<u>Figure</u>	<u>Page</u>
55. Effect of Segment Size on the Pressure-to-Strength Ratio, $p/\sigma_1$ , for the Ring-Fluid-Segment Container . . . . .	190
56. Effect of Segment Size on the Pressure-to-Strength Ratio, $p/\sigma_3$ , for the Ring-Fluid-Segment Container . . . . .	190
57. Effect of Support Pressure, $p_3$ , on Bore Pressure, $p$ , Capability for the Ring-Fluid-Segment Container . . . . .	192
58. Maximum Pressure-to-Strength Ratio, $p/\sigma_1$ , for the Pin-Segment Container . . . . .	192
59. Ratio of Interface Pressure Between Segments and Liner to Bore Pressure for the Pin-Segment Container . . . . .	193
60. Controlled Fluid-Fill Cylindrical-Layered Container [Reference (42)] . . . . .	195
61. Generalized Fatigue Relation in Terms of Shear Stresses . . . . .	198
62. Shear-Yield- and Shear-Fatigue-Strength Relations . . . . .	198
63. Influence of Pressures $p_N$ , $q_N$ and $q_0$ on the Pressure Capability $p_0$ . . . . .	202
64. Pressure-to-Strength Ratios for Single-Ring Container for $10^6$ - $10^7$ Cycles Life . . . . .	203
65. Comparison of Theory and Experiment for Single-Ring Containers . . . . .	203
66. Cross-Sectional View of Hydrostatic-Extrusion Tooling . . . . .	219
67. Cross-Sectional View of Container I . . . . .	222
68. Stress Pattern in Container I at Room Temperature . . . . .	223
69. Stress Pattern in Container I at 500 F . . . . .	224
70. Fractograph of Fractured Surface of Liner of Container I . . . . .	228
71. Electron Microscopic Fractograph Showing Fine Fatigue Striations in Liner of Container I . . . . .	230
72. Electron Microscopic Fractograph Showing Cleavage Fracture of Undissolved Carbides in Liner of Container I . . . . .	230
73. Cross-Sectional View of Container II. . . . .	232
74. Stress Pattern in Container II at Room Temperature . . . . .	233