

LIST OF SYMBOLS SECTION 3

A_n, B_n	= coefficients of materials in fatigue relations
N	= the total number of components in a container; N also denotes the outermost component
n	= a specific component when numbered from inside out; i. e., $n = 1, 2, \dots, N$
r_n	= outside radius of component n , inches
r_{n-1}	= inside radius of component n , inches
r_o	= bore radius of container, inches (inside radius of liner)
r_N	= outer radius of container, inches
k_n	= wall ratio of component n , $k_n = r_n/r_{n-1}$
K	= over-all wall ratio of container, $K = r_N/r_o = k_1 k_2 \dots k_N$
K'	= wall ratio of inner part of ring-fluid-segment container, $K' = r_3/r_o$
E_n	= modulus of elasticity of component n , psi
p_n	= pressure acting on component n at r_n when $p \neq 0$, psi
p_{n-1}	= pressure acting on component n at r_{n-1} when $p \neq 0$, psi
p	= bore pressure, psi, $p_o = p$ (internal pressure acting on the liner)
q_n	= residual interface pressure acting on component n at r_n when $p = 0$, psi
q_r	= residual interface pressure required at room temperature for a container designed for use at elevated temperature
q_{n-1}	= residual interface pressure acting on component n at r_{n-1} when $p = 0$, psi
S	= shear stress, psi
S_r	= semirange in shear stress for a cycle of bore pressure, psi
S_m	= mean shear stress for a cycle of bore pressure, psi
S_{min}	= minimum shear stress during a cycle of bore pressure, psi
S_{max}	= maximum shear stress during a cycle of bore pressure, psi
σ	= design tensile stress of ductile steel, psi ($\sigma \leq$ ultimate tensile strength)
σ_1	= design tensile stress of high-strength steel, psi ($\sigma_1 \leq$ ultimate tensile strength)
$(\sigma)_r$	= semirange in tensile stress for a cycle of bore pressure, psi

LIST OF SYMBOLS SECTION 3
(Continued)

- $(\sigma)_m$ = mean tensile stress for a cycle of bore pressure, psi
- σ_y = yield tensile stress, psi
- σ_u = ultimate tensile stress, psi
- $(\sigma)_{min}$ = minimum tensile stress during a cycle of bore pressure, psi
- $(\sigma)_{max}$ = maximum tensile stress during a cycle of bore pressure, psi
- σ_r = radial stress, psi
- σ_θ = circumferential stress, psi
- σ_z = axial (longitudinal) stress, psi
- α_r = semirange stress parameter for high-strength steel, $\alpha_r = (\sigma)_r / \sigma_1$
- α_m = mean stress parameter for a high-strength steel, $\alpha_m = (\sigma)_m / \sigma_1$
- M_1 = bending moment on ring segment
- M_2 = bending moment on pin segment
- u = radial displacement, inches
- v = circumferential displacement, inches
- ν = Poisson's ratio
- r, θ, z = cylindrical coordinates for radial, circumferential, and axial directions, respectively
- Δ_n = interference required (as manufactured) between cylinder, n , and cylinder, $n + 1$, inches
- Δ_{12} = interference required (as manufactured) between the liner, segments, and cylinder, 3, of the ring-segment and ring-fluid-segment containers, inches
- α_1, α_2 = coefficient of thermal expansion of material comprising rings 1 and 2