J. Phys. Soc. Japan 34 (1973) 1698

Dielectric Study of the Pressure Effect on the Cubic-Tetragonal Phase Transition in KMnF₃

Kazuo Gesi and Kunio Ozawa Japan Atomic Energy Research Institute, Tokai-mura, Ibaraki 319-11 (Received March 26, 1973)

At about 186 K, KMnF₃ undergoes a structural phase transition; the room temperature structure of cubic perovskite type (space group: Oh1) transforms to a tetragonal structure (space group: $D_{1b}^{(18)}$). The phase transition is caused by an instability of a soft zone boundary phonon of Γ_{25} mode at R-point of the reciprocal space.2) The mechanism of phase transition is therefore similar to that of 110 K transition in SrTiO3.3) Neutron diffraction study by Shirane et al.4) showed that the 186 K transition in KMnF3 is of the first order though it is very close to the second order one. Recently, one of the present authors (KG) found that there was a slight discontinuity of about 0.1 % in the low frequency dielectric constant accompanying the 186 K transition in KMnF₃.5) Then, the effect of hydrostatic pressure on the 186 K transition can be rather easily studied by dielectric constant measurements.

A (100) plate of which dimension was $0.25\,\mathrm{cm^2}\times0.35\,\mathrm{mm}$ was cut out of a single crystal block. After attached silver paste as the electrodes, the specimen was set in a Cu-Be high pressure bomb which had seven electrical terminal plugs. The pressure transmitting fluid used was 50-50 mixture of iso- and n-pentane. At a constant pressure, the dielectric constant was measured with a three terminal capacitance bridge as a function of temperature with an applied field of 25 $V_{\rm rms}$ at 1 kHz. Temperature was controlled with a liquid nitrogen bath, and measured with a copper-constantan thermocouple set closely around the specimen. Pressure was measured with a manganine gauge.

Figure 1 shows the temperature dependence of the




Fig. 1. Temperature dependence of the dielectric constant of (100) plate of KMnF₃ at various hydrostatic pressures. Frequency: 1 kHz.

•: on cooling, ×: on heating.

dielectric constant at different pressures. At the cubic-tetragonal phase transition point $T_{\rm c}$, a discontinuous change and a slight thermal hysteresis in each dielectric constant vs temperature curve are clearly seen. The transition temperature increases with




Fig. 2. Pressure dependence of the cubic-tetragonal phase transition temperature of KMnF₃ obtained from the dielectric constant measurements. The vertical bars indicate the thermal hysteresis during cooling and heating runs.

increasing hydrostatic pressure. Figure 2 shows the pressure dependence of the transition temperature. In the figure, the vertical bars represent the thermal hysteresis. Up to about 6 kbar, the $T_{\rm c}$ vs p relation is linear with a slope of ${\rm d}T_{\rm c}/{\rm d}p$ =2.63±0.09K kbar⁻¹. The value is slightly smaller than that of 3.5K kbar⁻¹ obtained by Okai and Yoshimoto⁶⁾ from a sound velocity measurement, but it is in good agreement with a thermodynamical expectation of 2.9 K kbar⁻¹. 7)

The authors would thank Professor K. Hirakawa of Tokyo University who kindly provided excellent single crystals of KMnF₃.

References

- V. J. Minkiewicz, Y. Fujii and Y. Yamada: J. Phys. Soc. Japan 28 (1970) 443.
- V. J. Minkiewicz and G. Shirane: J. Phys. Soc. Japan 26 (1969) 674.
- 3) G. Shirane and Y. Yamada: Phys. Rev. 177 (1969) 858.
- 4) G. Shirane, V. J. Minkiewicz and A. Linz: Solid State Commun. 8 (1970) 1941.
- 5) K. Gesi: unpublished data.
- B. Okai and J. Yoshimoto: J. Phys. Soc. Japan 34 (1973) 837.
- L. M. Reshchikova, V. I. Zinenko and K.S. Aleksandrov: Fiz. tverdogo Tela 11 (1969) 3448. translation: Soviet Physics-Solid State 11 (1970) 2893.

OCT 1 0 1973