

system records transit times and other information required for computing the elastic moduli.

5) Applications are primarily related to problems in determining basic knowledge about rock properties and the elastic behavior of rock systems under specified subsurface environmental conditions.

6) *P*-wave and *S*-wave velocities measured in samples of aluminum, Solenhofen limestone, and Boise sandstone are in good agreement with reliable published values.

#### APPENDIX

##### Angular Relationships at a Liquid-Solid Interface

When a *P* wave is incident in a liquid upon a plane liquid-solid interface, the relationships between the angle of incidence and the angles of refraction for *P* waves and *S* waves are given by Snell's Law:

$$\sin \alpha / \sin \epsilon = V_1 / V_p \quad (1)$$

$$\sin \alpha / \sin \beta = V_1 / V_s \quad (2)$$

##### Amplitude Ratios

Amplitude ratios of elastic waves reflected and refracted at solid-liquid interfaces in the dual-mode ultrasonic apparatus were computed from equations published by Ergin [25]. Equation (3) gives the amplitude ratio *c* of the reflected *P* wave when a *P* wave is incident in a solid (aluminum) against a liquid (oil).

$$c = \frac{\cos \eta (m_1 \cos^2 2\zeta - 1/m_1 \sin 2\theta \sin 2\zeta) - m_1 n_1 r_1 \cos \theta}{\cos \eta (m_1 \cos^2 2\zeta + 1/m_1 \sin 2\theta \sin 2\zeta) + m_1 n_1 r_1 \cos \theta} \quad (3)$$

Equation (4) gives the amplitude ratio *f* of the refracted *SV* wave when a *P* wave is incident in a liquid (oil) against a solid (aluminum).

$$f = \frac{2n_2/m_2 \sqrt{r_2 \sin 2\alpha \sin 2\beta \cos \epsilon}}{\cos \epsilon + n_2 r_2 \cos \alpha [1 - 2 \sin \beta \sin 2\beta (\cos \beta - 1/m_2 \cos \epsilon)]} \quad (4)$$

##### Elastic Moduli

The elastic moduli for isotropic elastic materials are computed from the relations [5] given below:

$$\text{bulk modulus } K = \rho_2 (V_p^2 - 4/3 V_s^2) \quad (5)$$

$$\text{bulk compressibility} = 1/K \quad (6)$$

$$\text{rigidity modulus} = \rho_2 V_s^2 \quad (7)$$

$$\text{Young's modulus} = 9\rho_2 V_s^2 m_3^2 / 3m_3^2 + 1 \quad (8)$$

$$\text{Poisson's ratio} = \frac{1}{2} [(m_1^2 - 2)/(m_1^2 - 1)] \quad (9)$$

#### REFERENCES

- [1] M. R. J. Wyllie, A. R. Gregory, and L. W. Gardner, "Elastic wave velocities in heterogeneous and porous media," *Geophysics*, vol. 21, pp. 41-70, 1956.
- [2] D. S. Hughes and H. J. Jones, "Elastic wave velocities in sedimentary rocks," *Trans. Am. Geophys. Union*, vol. 32, pp. 173-178, 1951.
- [3] M. R. J. Wyllie, A. R. Gregory, and G. H. F. Gardner, "An experimental investigation of factors affecting elastic wave velocities in porous media," *Geophysics*, vol. 28, pp. 459-493, 1958.
- [4] F. Birch, "The velocity of compressional waves in rocks to 10 kb. Part I," *J. Geophys. Res.*, vol. 65, pp. 1083-1102, 1960.
- [5] —, "The velocity of compressional waves in rocks to 10 kb. Part II," *J. Geophys. Res.*, vol. 66, pp. 2199-2224, 1961.
- [6] M. S. King, "Wave velocities in rocks as a function of changes in overburden pressure and pore fluid saturants," *Geophysics*, vol. 31, pp. 50-73, 1966.
- [7] A. R. Gregory, "Mode conversion technique employed in shear velocity studies of rock samples under axial and uniform compression," *Trans. AIME*, vol. 240, pp. 136-148, 1967.
- [8] A. L. Podio, A. R. Gregory, and K. E. Gray, "Dynamic properties of dry and water-saturated Green River shale under stress," *Soc. Petrol. Engrs. J.*, pp. 389-404, 1968.
- [9] G. H. F. Gardner, M. R. J. Wyllie, and D. M. Droschak, "Hysteresis in the velocity pressure characteristics of rocks," *Geophysics*, vol. 30, pp. 111-116, 1965.
- [10] W. P. Mason and H. J. McSkimin, "Attenuation and scattering of high frequency waves in metals and glasses," *J. Acoust. Soc. Am.*, vol. 19, pp. 464-473, 1947.
- [11] D. S. Hughes, W. L. Pondron, and R. L. Mims, "Transmission of elastic pulses in metal rods," *Phys. Rev.*, vol. 75, pp. 1552-1556, 1949.
- [12] D. S. Hughes and H. J. Jones, "Variation of elastic moduli of igneous rocks with pressure and temperature," *Bull. Geol. Soc. Am.*, vol. 61, pp. 843-856, 1950.
- [13] D. S. Hughes and J. H. Cross, "Elastic wave velocities in rocks at high pressures and temperatures," *Geophysics*, vol. 16, pp. 577-593, 1951.
- [14] D. S. Hughes and C. E. Cooke, "The effect of pressure on the reduction of pore volume of consolidated sandstones," *Geophysics*, vol. 18, pp. 298-309, 1953.
- [15] A. R. Gregory, "Shear wave velocity measurements of sedimentary rocks under compression," *Rock Mechanics*. New York: Pergamon, 1963, pp. 439-471.
- [16] K. Subbarao and B. Ramachandra Rao, "A simple method of determining ultrasonic velocities in rocks," *Nature*, vol. 180, p. 978, 1957.
- [17] M. R. J. Wyllie, G. H. F. Gardner, and A. R. Gregory, "Studies of elastic wave attenuation in porous media," *Geophysics*, vol. 27, pp. 569-589, 1962.
- [18] M. S. King and I. Fatt, "Ultrasonic shear-wave velocities in rocks subjected to simulated overburden pressure," *Geophysics*, vol. 27, pp. 590-598, 1962.
- [19] A. R. Gregory, "Ultrasonic pulsed-beam transmission and reflection methods for measuring rock properties—Some theoretical and experimental results," *Trans. 6th Ann. Logging Symp., SPWLA*, vol. 1, 1A, 1965.
- [20] J. van Steveninck, "Apparatus for simultaneous determination of longitudinal and shear wave velocities under pressure," *J. Sci. Instr.*, vol. 44, pp. 379-381, 1967.
- [21] M. S. King, "Static and dynamic elastic moduli of rocks under pressure," *Trans. ASME* (to be published).
- [22] K. P. Desai, "Sequential measurement of longitudinal and shear velocities of rock samples under triaxial pressure," Ph.D. dissertation, University of Tulsa, Tulsa, Okla., 1967.
- [23] R. E. Thill and T. R. Bur, "An automated ultrasonic pulse measurement system," *Geophysics*, vol. 34, pp. 101-105, 1969.
- [24] J. R. Frederick, *Ultrasonic Engineering*. New York: Wiley, 1965, pp. 33-35.
- [25] K. Ergin, "Energy ratio of the seismic waves reflected and refracted at a rock-water boundary," *Bull. Seism. Soc. Am.*, vol. 42, pp. 349-372, 1952.
- [26] W. P. Mason, *Physical Acoustics and the Properties of Solids*. New York: Van Nostrand, 1958, p. 96.
- [27] N. Grossman, "New methods determine grain size ultrasonically," *Iron Age*, pp. 72-75, December 31, 1953.
- [28] H. C. Heard, "Transition from brittle fracture to ductile flow in Solenhofen Limestone as a function of temperature, confining pressure, and interstitial fluid pressure," *Rock Deformation*, GSA Memo. 79, pp. 193-226, 1960.
- [29] L. Peselnick, "Elastic constants of Solenhofen Limestone and their dependence upon density and saturation," *J. Geophys. Res.*, vol. 67, pp. 4441-4448, 1962.

Reprinted by permission from  
IEEE TRANSACTIONS ON SONICS AND ULTRASONICS

Vol. Su-17, No. 2, April 1970

Copyright © 1970, by the Institute of Electrical and Electronics Engineers, Inc.

PRINTED IN THE U.S.A.