

In this equation X_n is the fractional area occupied by the n th flow unit on the shear surface, $\alpha_n = (\lambda\lambda_2\lambda_3)_n/2kT$ and $\beta_n = 1/[(\lambda/\lambda_1)2k']_n$, where k is Boltzmann's constant, T the temperature, and the summation is the extension to all the flow units present. Here $\lambda_2\lambda_3$ is the cross-sectional area of a certain flow unit, λ the distance a unit moves between equilibrium positions, λ_1 the distance between planes of flow units of a certain kind, and k' the rate constant for passage of the unit over a potential energy barrier.

The experimental data of greases are explained in terms of Newtonian and non-Newtonian flow units, e.g.,

$$f = X_1\beta_1/\alpha_1\dot{s} + X_2/\alpha_2 \sinh^{-1}\beta_2\dot{s}. \quad (27)$$

The subscripts 1 and 2 refer to the Newtonian and non-Newtonian units, respectively. If it is assumed that $X_1\beta_1/\alpha_1 \ll X_2\beta_2/\alpha_2$ (the inequality is due to the fact that $\beta_1/\alpha_1 \ll \beta_2/\alpha_2$ while $X_1 \gg X_2$) then (6) becomes

$$f = X_2/\alpha_2 \sinh^{-1}\beta_2\dot{s}. \quad (28)$$

Pressure increases and decreases effect an equilibrium transition between Newtonian and non-Newtonian flow. Thus when $X_1 \gg X_2$,

$$X_2 \cong \exp(-\Delta F/RT)$$

and from (1)

$$\begin{aligned} X_2 &= \exp(-\Delta F_0/RT) \exp(-P\Delta V/RT) \\ &= K_0 \exp(-P\Delta V/RT), \end{aligned} \quad (29)$$

where K_0 is the equilibrium constant when $P=0$. Also

$$\begin{aligned} \beta_2 &= (\lambda 2k'/\lambda_1)_2^{-1} = (\lambda/\lambda_1 2kT/h)_2^{-1} \exp(\Delta F^\ddagger/RT) \\ &= \beta_{2,0} \exp(P\Delta V^\ddagger/RT), \end{aligned} \quad (30)$$

where

$$\beta_{2,0} = (\lambda/\lambda_1 2kT/h)^{-1} \exp(F_0^\ddagger/RT).$$

Substituting Eqs. (29) and (30) into (28) yields

$$f = [K_0/\alpha_2 \exp(-P\Delta V/RT)] \sinh^{-1} \times [\beta_{2,0} \exp(-P\Delta V^\ddagger/RT)\dot{s}], \quad (31)$$

which is the equation of flow under pressure.

By applying (31) to the \dot{s} - f flow curves discussed earlier, the factors X_2/α_2 and β_2 are obtained. ΔV is obtained from the slope of the line in the plot of $\ln(X_2/\alpha_2)$ against P . Similarly ΔV^\ddagger is determined from the plot of $\ln\beta$ against P . $\beta_{2,0}$ is evaluated by extrapolating the β_2 values obtained at various pressures to $P=0$. Finally, in (30), ΔF^\ddagger is readily calculated for $\lambda \cong \lambda_1$.

APPLICATION TO LUBRICANT

Figure 18 shows the theoretical and experimental flow curve for Calresearch 60R-588 grease (obtained from the California Research Corporation) under a pressure of 339 atm. The shear rate \dot{s} is determined by Eq. (25) and the stress f by the relation $f = r\Delta P/2L$. The reproducibility of the experimental result is within a range of two percent. The theoretical flow curve was calculated from Eq. (27). The factors $X_1\beta_1/\alpha_1$, X_2/α_2 , and β_2 were determined using Eyring's well-known method.³⁵

ACKNOWLEDGMENTS

It is a pleasure to thank the National Science Foundation and the American Chemical Society for joint support of this work. The initial work on the cylinder assembly was done by R. H. Woolley.

The authors also express their thanks to Professor Tracy Hall for helpful discussions concerning pressure effects in Part II, to Mr. Fred Straub for machine work, and to Miss Nola McKee for technical assistance with calculations, the preparation of the drawings and the manuscript.