

- 5032 Claflin W M  
THE EXPERIMENTAL DETERMINATION OF THE DYNAMIC  
STRUCTURAL RESPONSE OF AN AIRPLANE TO IMPACT  
LOADINGS  
Proceedings Society for Experimental Stress Analysis  
1947, Vol. V, No. 1, pp. 31-38.
- 5033 Welch W P  
A PROPOSED NEW SHOCK MEASURING INSTRUMENT  
Proceedings Society for Experimental Stress Analysis  
1947, Vol. V, No. 1, pp. 39-51.
- 5034 Pederson A H and MacCarthy J G  
DETERMINATION OF THE EFFECT OF GROUND IMPACT FORCES  
IN THE AIRPLANE DROP TEST  
Proceedings Society for Experimental Stress Analysis  
1947, Vol. V, No. 1, pp. 122-136.
- 5035 Mindlin R D, Stubner F W and Cooper H L  
RESPONSE OF DAMPED ELASTIC SYSTEMS TO TRANSIENT  
DISTURBANCES  
Proceedings Society for Experimental Stress Analysis  
1947, Vol. V, No. 2, pp. 69-87.
- 5036 Leal O N, Bisplinghoff R L and Pian T H H  
STUDIES OF TRANSIENT STRESSES IN AN AIRPLANE MODEL  
WING DURING DROP TESTS  
Proceedings Society for Experimental Stress Analysis  
1948, Vol. VI, No. 1, pp. 115-122.
- 5037 Nisbet J S and Brennan J N  
SOME SECONDARY EFFECTS RELATED TO IMPACT WAVE  
FORMS  
Journal of the Acoustical Society of America  
1957, Vol. 29, pp. 837-842.
- This paper is a theoretical analysis of simple structures  
under various types of applied impact. The results are  
presented from the standpoint of a static acceleration  
which would be required to produce the same maximum  
response in an undamped single degree of freedom system.
- Reference is made to similar work by Frankland  
Proceedings SESA, 1948, Vol. VI, No. 2, pp. 7-27.
- 5038 Gerard G and Becker H  
COLUMN BEHAVIOR UNDER CONDITIONS OF IMPACT  
Journal of the Aeronautical Sciences  
1952, Vol. 19, pp. 58-60.

- 5039 Meier J H  
ON THE DYNAMICS OF ELASTIC BUCKLING  
Journal of the Aeronautical Sciences  
1945, Vol. 12, pp. 433-440.
- 5040 Hoff N J  
THE DYNAMICS OF THE BUCKLING OF ELASTIC COLUMNS  
Journal of Applied Mechanics, Trans. ASME  
1951, Vol. 73, pp. 68-74.
- 5041 Kornhauser M  
PREDICTION AND EVALUATION OF SENSITIVITY TO TRAN-  
SIENT ACCELERATIONS  
Journal of Applied Mechanics, Trans. ASME  
1954, Vol. 76, pp. 371-380.
- 5042 Orowan E  
CONDITION OF HIGH-VELOCITY DUCTILE FRACTURE  
Journal of Applied Physics  
1955, Vol. 26, pp. 900-902.
- The Griffith energy criterion,  $dW = -dU$  ( $dW$  = crack propagation work,  $-dU$  = released elastic energy), cannot be applied to essentially ductile fractures. In particular, it does not represent the condition of rapid ductile fracture propelled by the elastic energy of the specimen. The condition of such fractures is  $d^2W/dx^2 = -d^2U/dx^2$ , where  $x$  is the plastic extension accompanying the propagation of the crack.  
(Author's abstract)
- 5043 Fung Y C and Barton M V  
SOME SHOCK SPECTRA CHARACTERISTICS AND USES  
Journal of Applied Mechanics, Trans. ASME  
Vol. 80, pp. 365-372.
- 5044 Flynn P D  
ELASTIC RESPONSE OF SIMPLE STRUCTURES TO PULSE  
LOADING  
Ballistic Research Laboratories, Memorandum Report No. 525.

This paper deals with the elastic response of some simple structures subjected to a pulse loading. The structures considered are the mass on a spring, the simply supported beam, the cantilever, the circular membrane, and the clamped circular plate. The loading considered is that of a triangular pulse of pressure uniformly distributed over the area of the structural normal to the direction of motion. The pressure jumps to its peak value instantaneously and falls off linearly with increase in time, reaching