

25. Autoclave "Slimline" 15,000 psi fittings and valves for 9/16 in. x 5/16 in. pressure tubing as follows:
 - a. nipples, 4 in., 5 ea.
 - b. cross, 2 ea.
 - c. tee, 3 ea.
 - d. elbow, 6 ea.
 - e. adapter, tubing to 1/4 in. NPT male, 1 ea.
 - f. adapter, tubing to 3/8 in. NPT male, 1 ea.
 - g. valve, 2-way angle, 2 ea.
 - h. valve, 2-way straight, 2 ea.
 - i. gland, 45 ea.
 - j. collar, 45 ea.
26. Sprague pump: 1 ea., no. S-216C-300.
27. Air mufflers; 2 ea., Sprague Engineering Co., Model 0-5.
28. Lubro control unit: 1 ea., Sprague no. P/N 21-009-002 (for use with pump).
29. Relief valve: 1 ea., Sprague no. 005-023A-1.
30. Oil reservoirs: 2 ea., welded steel cans, 8 in. O.D. x 20 in. long x 3/16 in. wall with one 1/2 in. NPT female side oil outlet 1 in. from bottom and one 1/2 in. NPT female top outlet near rim for air inlet, and also 1-1/2 in. NPT female top outlet near rim with pipe plug for filling.
31. Air filter, regulator unit: 1 ea., Sprague, model 0-7 without lubricator (for oil reservoirs).
32. Air valve, 1/2 in. NPT (to control Sprague pump), panel mount, Lukenheimer Fig. 907BS.
33. Air valve, 1 ea., (to admit and exhaust air to reservoirs), plug, Republic no. 721-4Tx four way reversing, flanged, 1/2 in. tube connections for air service, lubricant # 3.