

- 15. Leather back-up washers for item 14 above, 8 ea., Chicago Rawhide Co., part number - 70, 3 in. O.D. x 7-1/2 in. I.D. x 1/8 in. thick.
- 16. O-ring (seal A): 4 ea., Series no. 9021-445, Buna N compound, 90 shore durometer, 8.5 in. O.D. x 1/4 in. wide.
- 17. O-ring (seal C): 4 ea., same as item 14.
- 18. O-ring (seal D): 4 ea., Series no. 9021-345, Buna N compound, 90 shore durometer, 4-3/8 in. O.D. x 3/16 in. wide.
- 19. Retainer ring hold-down screws: 48 ea., 1/2" -20 thd. x 3" long, socket head cap screws.
- 20. Cylinder top plate hold down screws: 48 ea., 3/8" - 16 thd. x 1-1/2" long, socket head cap screws.
- 21. Positioner hold-down screws: 20 eac., size 10-32 x 1-1/2 in. long, socket head cap screws.
- 22. Binding ring hold-down screws: 12 ea., 1/4" ⁻²⁰ x 1-1/2 in. long, socket head cap screws.
- 23. Guide pins: 4 ea., 1.2500 ± 0.0000 - 0.0001" diam. x 7 in. long, Lamina no. TN-125.
- 24. Pressure tubing: 3 lengths, stainless steel 9/16 in. O.D. x 5/16 in. I.D. x 20 ft.
- 25. Autoclave "slimline" 15,000 psi fittings and valves for 9/16 in. x 5/16 in. pressure tubing as follows:
 - a. nipples, 4 in., 5 ea.
 - b. cross, 2 ea.
 - c. tee, 3 ea.
 - d. elbow, 6 ea.
 - e. adapter, tubing to 1/4 in. NPT male, 1 ea.
 - f. adapter, tubing to 3/8 in. NPT male, 1 ea.
 - g. valve, 2 - way angle, 2 ea.
 - h. valve, 2-way straight, 2 ea.
 - i. gland, 45 ea.
 - j. collar, 45 ea.
- 26. Sprague pump: 1 ea., no. S-216C-300.
- 27. Air mufflers: 2 ea., Sprague Engineering Co., Model 0-5.
- 28. Lubro control unit: 1 ea., Sprague no. P/N 21-009-002 (for use with pump).

Salt Lake City

Autoclave Engineers 5605 - 2nd W.

~~A.E.~~

~~A.E.~~

Alta Engineering
937 E. - 9th So.
Salt Lake

~~Alta~~
~~Alta~~
~~Alta~~

→ k. adapter, 1 ea., # 155A-9401, tubing to 1/4" NPT male.