

Anvils, " Sept. 19, 1962.

11. Ditto, 3/4 in. size.

12. Ditto, 1 in. size.

3 in. O.D. x 2 in I.D. x 1.5 in long

13. Piston-rod nut: 4 ea., low alloy steel, ~~hex or spanner type, 16 T.P.I.~~

14. O-ring (seal ^B ~~A~~): 4 ea., Series no. 9021-443, Buna N compound, 90 Shore durometer hardness, 8 in. O.D., 1/4 in. wide.

15. Leather back-up washers for item 14 above, 8 ea., Chicago Rawhide Co., part number-70, 8 in. O.D. x 7-1/2 in. I.D. x 1/8 in. thick,

16. O-ring (seal ^A ~~B~~): 4 ea., Series no. 9021-⁴⁴⁵~~74~~, Buna N compound, 90 Shore durometer, ^{8.5}9 in. O.D. x 1/4 in. wide.

17. O-ring (seal C): 4 ea., same as item 14.

18. O-ring (seal D): 4 ea., Series no. 9021-345, Buna N compound, 90 Shore durometer, 4-3/8 in. O.D. x 3/16 in. wide.

19. ~~Leather back-up washers for item 18 above: 8 ea., Chicago Rawhide Co., part no. -48, 4-3/8 in. O.D. x 4 in. I.D. x 0.094 in. thick.~~

20. Cylinder top plate hold down screws: 48 ea., 3/8 in. -16 x 1-1/2 in. long, socket head cap screws.

21. Positioner hold-down screws: 20 each, size 10-32 x 1-1/2 in. long, socket head cap screws.

22. Binding ring hold-down screws: 12 ea., 1/4 - 20 x 1-1/2 in. long, socket head cap screws.

23. Guide Pins: 4 ea., 1.2500 + 0.0000 - 0.0002¹/₂ in diam. x 7-~~1/4~~ in. long, Lamina no. TN-125. ~~with 1/8 in. radius each end. "Case 60-Hardened and Ground".~~

24. Pressure tubing: 3 lengths, stainless steel 9/16 in. O.D. x 5/16 in. I.D. x 20 ft.

→ Retainer Ring hold-down screws: 48 ea, 1/2"-20 thd x 3" long, socket head cap screws.