

- alt*
B44
29. Relief valve: 1 ea., Sprague no. 005-023A-1.
30. Oil reservoirs: 2 ea., welded steel cans, 8 in. O. D. x 20 in. long x 3/16 in. wall with one 1/2 in. NPT female side oil outlet 1 in. from bottom and one 1/2 in. NPT female top outlet near rim for air inlet, and also 1-1/2 in. NPT female top outlet near rim with pipe plug for filling.
- alt*
31. Air filter, regulator unit: 1 ea., Sprague model 0-7 without lubricator (for oil reservoirs).
- alt*
32. Air valve, 1/2 in. NPT (to control Sprague pump), panel mount, Lukenheimer Fig. 907BS.
- alt*
33. Air valve, 1 ea., (to admit and exhaust air to reservoirs), plug, Republic no. 721-4Tx four way reversing, flanged, 1/2 in. tube connections for air service, lubricant # 3.
- Crane Co.*
Primo
34. Pipe fittings (galvanized) as follow:
- a. street elbows, 3/8 in., 6 ea.,
 - b. elbows, 3/8 in. 4 ea.
 - c. short nipples, 3/8 in., 4 ea.
 - d. Tees, 3/8 in., 2 ea.
 - e. cross, 3/8 in., 1 ea.
 - f. elbows, 1/2 in., 4 ea.
 - g. street elbows, 1/2 in., 2 ea.
 - h. tees, 1/2 in., 2 ea.
 - i. short nipples, 1/2 in., 4 ea.
 - j. 3/8 in. pipe, galvanized, 1 length.
 - k. 1/2 in. pipe galvanized, 1 length.
- alt*
35. Parker, Push-lok-82 fittings and hose as follows:
- a. Push-lok 3/8 - 3/8 - 30182-4, 8 ea.
 - b. Push-lok 3/8 - 6 - 30682 - 4, 8 ea.
 - c. Push-lok hose # 3/8 - 831, 20 ft.
 - d. Push-lok 1/2 - 1/2 - 30182-4, 6 ea.
 - e. Push-lok 1/2 - 8 - 30682-4, 6 ea.
 - f. Push-lok hose # 1/2-831, 20 ft.
- alt*
36. Tubing to pipe adapter, 3/8 NPT to 3/8 - 37°, straight through, Parker no. 6-6-0103-1, 8 ea.